AT-5000ES

GROWATT US Split Phase Transformer

- AT-5000ES comes with built-in transformer
- AT-5000ES has a maximum sum of L1-N and L2-N simultaneous output is 5000VA
- Maximum continuous power is 5.0kw for energy storage



POWER-INGO TOMO-RROW

GROWATT

www.ginverter.com

Product model	AT-5000ES
Input Data	
Normal Voltage	240V/208V
Normal Frequency	50/60Hz
Max. Power	5000VA
Max. Current	21/24A
Output Data	
Split Phase Data	
Rated Power(L-L)	5000VA
Rated unbalanced power(L-N)	2500W
Output voltage	120/240Vac and104/208Vac
Max continued current(L-L)	21/24A
Max continued current(L-N)	(21/24A)*2
General Data	
Cooling	Natural Convection
Ingress Protection	IP20
Installation	Wall Mountable
Operating Temperature Range	-25~+55°C(-13 ~ +131°F)
Weight	13.5kg/30lb
Dimensions（W/H/D）	15.16/8.27/4.13in(385/210/105mm)
Warranty	5 Years

The rated power of secondary side L1-N and L2-N could up to 5kVA respectively, and the power difference between the two split phases can not exceed 2.5kW.

SHENZHEN GROWATT NEW ENERGY CO.,LTD. A: 4-13/F,Building A,Sino-German(Europe)Industrial Park,Hangcheng Ave,Bao'an District,Shenzhen,China
T: + 86 755 2747 1900 F: + 86 755 2749 1460 E: info@ginverter.com