

WIT 28-55kW Hybrid Inverter

WIT 28-55K-HU-US L2

- Scalable system configuration, extend to 165kW
- Support UPS function and black start
- 100% unbalanced load when backup
- 110% continuous AC overloading capacity
- Support remote control of DG
- Grid-support functions



Preliminary Version

P O W E R
- I N G
T O M O -
R R O W O

GROWATT

<https://us.growatt.com>

Datasheet	WIT 28K-HU-US L2	WIT 35K-HU-US L2	WIT 40K-HU-US L2	WIT 55K-HU-US L2
Input Data (PV)				
Max. recommended PV power (for module STC)	54kW	75.6kW	86.4kW	108kW
Start voltage			195V	630V
Max. open circuit voltage of PV*1			360V, 180V-550V	
MPPT nominal voltage/range			32A	
Max. input current per MPP tracker			40A	
Max. short-circuit current per MPP tracker			2	
No. of PV strings per MPP tracker			8	10
No. of MPP trackers	5	7		
Output Data (AC)				
AC nominal power/max. AC apparent power	28kW/30.8kVA	35kW/38.5kVA	40kW/44kVA	55kW/60.5kVA
Nominal AC voltage/range			208V/220V, -15%~10%	
AC grid frequency/range			60Hz, 55-65Hz	
Max. output current	85.6A@208V 80.8A@220V	106.9A@208V 101A@220V	122.2A@208V 115.5A@220V	168.1A@208V 158.8A@220V
Adjustable power factor			-1...+1	
THDi			<3% (@100% load)	
AC grid connection type			3P3W+PE/3P4W+PE	
Input Data (AC)				
AC nominal power	56kW	70kW	80kW	110kW
Max. AC apparent power	56kVA	70kVA	80kVA	110kVA
Nominal AC voltage/range			208V/220V, -15%~10%	
Nominal AC grid frequency/range			50/60Hz, 45-55Hz/55-65Hz	
Nominal input current	155.6A@208V 147A@220V	194.4A@208V 183.7A@220V	222.2A@208V 210A@220V	305.6A@208V 288.7A@220V
Max. input current	155.6A@208V 147A@220V	194.4A@208V 183.7A@220V	222.2A@208V 210A@220V	305.6A@208V 288.7A@220V
Backup Power (AC power)				
AC nominal power/Max. AC apparent power	28kW/33.6kVA	35kW/42kVA	40kW/48kVA	55kW/66kVA
Max. single phase power	9.3kW	11.6kW	13.3kW	18.3kW
Nominal AC voltage			120V/127V(L-N), 208V/220V(L-L)	
Nominal AC frequency			50/60Hz	
Max. output current	93.3A@208V 88.2A@220V	116.7A@208V 110A@220V	133.3A@208V 126A@220V	183.3A@208V 173.2A@220V
Overload capability			≤110%: Continues; 110%~120%: <10min; >120%: 200ms	
Load unbalance			100%	
THDv			<3% (Linear load)	
On/off grid transfer time			≤16.6ms	
Battery Data (DC)				
Battery voltage range			380V-650V, recommended @ 512V	
Max. charging / discharging current	79A	99A	113A	156A
Continuous charging / discharging power	31.7kW	39.7kW	45.3kW	62.3kW
BMS communication			RS485/CAN	
Types of battery			Lithium /Lead-acid (Check third-party battery compatibility in the Approved Battery List)	
Efficiency				
Max. efficiency			98.2%	
Protection Devices				
PV reverse polarity protection			Yes	
Battery reverse protection			Yes	
AC/DC surge protection			Type II	
Insulation resistance monitoring			Yes	
Ground fault monitoring			Yes	
Grid monitoring			Yes	
Residual-current monitoring unit			Yes	
AC short-circuit protection			Yes	
String monitoring			Yes	
Anti-islanding protection			Yes	
PID protection			Yes	
AFCI function			Opt	
General				
Dimensions (W/H/D)			33.5/53.1/20.1inch (850/1350/510mm)	
Weight	153kg/337.3lbs		160kg/352.7lbs	
Operating temperature range			-22°F~+140°F, >122°F derating	
Altitude			13123ft(4000m)	
Topology			Transformerless	
Cooling			Smart air cooling	
Enclosure			IP66/NEMA 4X	
Display			OLED+LED/WIFI+APP	
Interfaces:RS485/CAN			Yes	
Interfaces:WIFI//4G/LAN			Opt	
Warranty: 5 / 10 years			Yes/Opt	

UL1741:2021, UL1741 SA/SB:2020, IEEE1547:2018, IEEE1547.1:2020, HECO Rule14, E-5000, CSIP, SA17-SA18, UL1998:2018, CEC, FCC Part 15, CSA C22.2.107.1

*1 The maximum open circuit voltage of PV string must be lower than the maximum input voltage of the battery system connected to the inverter.
SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. All specifications are subject to change without notice.